

# **Splice trays**

## **Specifications:**

**Splice Cassette KNS-12** 

Store capacity: up to 12 fusion splices Dimension: 162 x 124 x 8 mm

Material: plastic

Standard: splice holder (2 pcs, heat-shrink)

cable tie (4 pcs)

Options: lid



### Splice Cassette 2S-1000

Store capacity: up to 12 fusion splices

Dimension: 145 x 95 x 8 mm

Material: plastic Standard: lid

cable tie (4 pcs)

Options: splice holder (2 pcs, heat-shrink)



# Splice Cassette - TC 251S series

Dimensions: 195 x 116 x 10 mm

Weight: 115 g

Store capacity: up to 16 fusion splices Material: Noryl (LSZH plastic)

### TC 251S-1X

Standard components:

- Splice holder (2 pcs, heat-shrink, TC250S-10)
- Loose tube clamps with rubber padding
- Cable tie (4 pcs)
- Optional components: lid, other type of splice holder



## Splice Cassette - TC 251S series

Dimensions: 195 x 116 x 10 mm

Weight: 115 g

Store capacity: up to 16 fusion splices Material: Noryl (LSZH plastic)

### TC 251S-1

- Standard components:
- Splice holder (2 pcs, heat-shrink, TC250S-10)
- Cable tie (4 pcs)
- Optional components: lid, other type of splice holder





# **Splice Cassette TC 250S series**

dimensions: 143 x 96 x 10 mm

weight: 80 g

store capacity: up to 12 fusion splices material: Noryl (LSZH plastic)

### TC250S-1X

Standard components:

- Splice holder (1 pcs, heat-shrink, TC250S-13)
- · lLose tube clamps with rubber padding
- Cable tie (4 pcs)
- · Optional components: lid, other type of splice holder



# Splice Cassette TC 250S series

dimensions: 143 x 96 x 10 mm

weight: 80 g

store capacity: up to 12 fusion splices material: Noryl (LSZH plastic)

#### TC250S-1

Standard components:

- Splice holder (1 pcs, heat-shrink, TC250S-13)
- Cable tie (4 pcs)
- · Optional components: lid, other type of splice holder



## **Drawer Equipment Splice TC 248S**

#### Variants:

TC 248S - 4 4 splice cassettes
TC 248S - 6 6 splice cassettes
TC 248S - 8 8 splice cassettes
TC 248S - 12 12 splice cassettes

Store capacity: up to 12 fusion splices per cassette

Material: Noryl (LSZH plastic)

## Description:

Easy acces to fibre in lower trays (locking arm)

Loose tube and pigtail clamps pigtail lock/organizer

### Standard components:

- Splice holder TC250S-2, 2 pcs per cassette
- (up to 3.0 mm, 6 heat-shrink splices)
- Fiber cover (18 pc)
- Marking sticker

Optional components: other type of splice holder





## TC 250S/251S/248S series-Splice holders













(6 sleeves Ø 3 mm)



TC250S-2

TC250S-4

TC250S-7

51S-8 TC250S-10

2508-10

TC250S-12 (12 sleeves Ø 1.55 mm

or crimp protections)







Note:

For TC 250S series suitable: TC250S-13, TC250S-12, TC250S-2, TC250S-10

For TC 248S series suitable: TC250S-2, TC250S-4, TC250S-7, TC251-10

TC250S-13

S-13 TC250S-14

TC250S-30

(6 sleeves Nortel) (5 couplers, Ø 3.6 mm) (5 mechanical splices, 3M) (8 sleeves Ø 3 mm)

(12 sleeves  $\emptyset$  2,6 mm) (12 sleeves  $\emptyset$  2.8 mm)

(4 sleeves Ø 3 mm)

## **Splice Bridge TC2501A**

store capacity: 6 splice slots (up to 8 splices per slot)

description: easy mounting - sticker

application: OPTOKON Cable Management System

dimensions: 35 x 30 x 27 mm

