

MCPE-02 End User Terminating Box

Description:

The OPTOKON MCPE-02 box introduces the wall mount, two fibers box, which is designed for optical cable termination in the customer premises – end user site in FTTH projects. The MCPE-02 box includes the holder for two splice protection sleeves. The internal fiber guides ensure the arrangement of the fiber reserve and its protection against smaller bending radius than allowed. The MCPE-02 allows installation of two SC single coupling adapters.




Features:

- Small dimensions
- Easy access to fibers
- Protection of conectors against damage
- Standard SC single or duplex adapters

Specifications:

ABS
Grey (RAL 7035) or White (RAL 9010)
-40°C to +75°C (acc. EN 60068-2-1 and EN 60068-2-1)
UL94 HB
IP42 (according IEC 60529)
120 x 100 x 26.5 mm (LxWxH)
95 g (without adapters and pigtails)





MCPE-02-SC A/SC S-A two single adapters



MCPE-02U storage box

Standard accessories:

MCPE-02 body, Cover, Splice cassette, Lid, Cable ties - 2 pcs Mounting screws, wall plastic plugs

Optional:

MCPE-02U Storage Box

The Storage box is mounted between the wall outlet and the wall. Is designed for overlength storage of the

is a registered trademark of OPTOKON, a.s. Other names and trademarks mentioned herein may be the trademarks of their respective owners. OPTOKON, a.s. reserves the right to make changes, without notice, to the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON a.s., Červený Kříž 250, 586 01 Jihlava, Czech Republic, tel. +420 564 040 111, WWW.OPTOKON.COM, SALES@OPTOKON.COM 2020-04-22



income cable which will be feed into the wall outlet. The storage box can accommodate an overlength of 4 meters (duplex cable) or 8 meters (simplex cable) and assures through its shape a minimal bending radius of 30 mm.

Specifications		
Material	ABS	
Colour	Grey (RAL 7035) or White (RAL 9010)	
Storage capacity	4 meters (duplex cable) 8 meters (simplex cable)	
Dimensions	120 x 100 x 18 mm (LxWxH)	100 120
Weight	40 g	


Pigtails¹:

USC-09 SM-PS-001	SC/PC, SM ultra polished, semitight, 1 m length
NSC-09 SM-PS-001	SC/APC, SM angle polished, semitight, 1 m length
ULC-09 SM-PS-001	LC/PC, SM ultra polished, semitight, 1 m length
NLC-09 SM-PS-001	LC/APC, SM angle polished, semitight, 1 m length

Adapters¹:

A-SC/PC-01-01 BL-01	SC/PC blue, zirconia sleeve
A-SC/APC-01-01 GR-01	SC/APC green, zirconia sleeve
A-LC-D/PC-01-01 BL	duplex LC/PC blue, zirconia sleeve

Splice protection sleeves: For up to 2 splice protection use standard sleeves P-A-40 Note: 1) Other types on request



MCPE-02-SC A/SC S-A two SC pigtails



Closed MCPE-02

Ordering code:

MCPE-02	
---------	--

XXX X			- X		
Coup	ling type			Sp	lice number
sc	SC	Μ	Multimode	A	standard (1-2 sleeves)
DLC	duplex LC	S	Singlemode		
NC	no connectors	Α	APC		

🥙 is a registered trademark of OPTOKON, a.s. Other names and trademarks mentioned herein may be the trademarks of their respective owners. OPTOKON, a.s. reserves the right to make changes, without notice, to the products described in this document, in the interest of improving design, operational function and/or reliability. OPTOKON a.s., Červený Kříž 250, 586 01 Jihlava, Czech Republic, tel. +420 564 040 111, WWW.OPTOKON.COM, SALES@OPTOKON.COM