

OFT-920 Ruggedized Optical Test Set

Description:

The OFT-920 ruggedized optical test set is designed for testing of optical networks terminated with connectors operating in harsh environment. It combines both light source and optical power meter in one common box. The test set is designed to meet the mining, petrochemical and broadcast industry demand. The ruggedized aluminium case makes the unit ideal for field operation. The memory capacity allows storage and uploading of up to 2000 measurements including memory position or fiber number, wavelength, absolute value or relative value and insertion loss. The tester supports memory download and test report generating. The rechargeable battery ensures long term working with minimal operation costs.



Features:

- Expanded Beam and ferrule technology harsh environmental connectors
- Ruggedized aluminium case
- Multimode (MM) and/or single mode (SM) applications
- Simultaneous testing of all 2/4 fibers
- Internal memory
- Displayed units: dBm, dB
- High dynamic range
- Various light sources combinations
- Built-in charger, battery status indicator
- Easy to use with menu navigation

Specifications:

Light Source:

Output power		Note:
850 nm, 1300 nm	-26 dBm (62.5/125 μ m fiber)	
1310, 1490, 1550, 1625 nm	-16 dBm	typ. value
Stability (1 hour, delta/2):		
850 nm, 1300 nm	± 0.03 dB	tested after 20 min warm up
1310, 1490, 1550, 1625 nm	± 0.05 dB	temperature $23 \pm 1^\circ$

Power Meter:

Photodetector	1 mm InGaAs	
Working wavelengths	MM: 850, 1300 nm SM: 1310, 1490, 1550, 1625 nm	can be customized
Uncertainty	$\pm 12\%$	1310, 1550 nm @ -20 dBm


Resolution	0.1	
Dynamic range	-55 dBm to +10 dBm -53 dBm to +17 dBm	1300, 1310, 1490, 1550, 1625 nm 850 nm

General specifications:

Dimensions	145 x 145 x 56 mm	without connectors
Weight	400 g	with battery
Temperature operating	-10 to +50 °C	
Temperature storage	-40 to +70 °C	
Humidity (non condensing)	0 to 95%	
IP rating	IP 54	
Battery working time	> 20 hrs	between battery charging

Application:

- Optical networks measurements
- Fiber continuity testing



temperature drift of output level

Standard Accessories:

- Power charging adaptor and USB Cable
- Soft carrying case
- Cleaning swabs

Ordering code:

OFT-920 - **XX** - **XXXX** - **XXX**

M5 (MM)	MM 50/125 mm
M6	MM 62.5/125 mm
SM	Singlemode

Source wavelength
as below

	Connector type²
HMA2	HMA ¹ Expanded Beam connector (non-contact optics), 2 fibers
HMA4	HMA ¹ Expanded Beam connector (non-contact optics), 4 fibers

- Note: 1) HMA-J compatible
2) Other connector types available on request

light source code	Description ³	application
650	650 nm visible laser	visual checking
850	850 nm	MM fiber testing
30	1300 nm	
850-30	850 nm + 1300 nm	
31	1310 nm	SM fiber testing
55	1550 nm	
62	1625 nm	
31-55	1310 + 1550 nm	

Note: 3) other wavelengths and port combinations on demand



Accessories:



Soft carrying case



Complete test set, including: OFT-920 tester, power charging adaptor, soft carrying case, USB Cable, reference patchcord⁴

Note: 4) reference patchcord - would be ordered according to STR_03-10_EN-HMA_Master

Options: Reference patchcord