

## OFDU-CAP-J

### Description:

The OFDU-CAP-J cabinet is primarily intended for convenient placement of CAPM cassettes. The unified modular system enables easy storage and fastening CAPM cassettes and can be extended according to operator needs. The OFDU-CAP-J terminates up to 288 fibers in a 3U distribution frame. This unit can take up to 12 prewired CAPM cassettes. The OFDU-CAP-J cabinet is produced from Aluminium alloy 5754 material. Benefits are excellent corrosion resistance and very high strength.



### Features:

- Arranged termination of fibers in CAPM cassettes
- Easily removable front metal cover
- Up to 288 fiber termination
- Easy access to each cassette
- Prewired CAPM cassettes include connectorized fiber pigtails and adapters
- Durable powder coat finish light grey colour (RAL7038, RAL 9006)
- Optional material-Aluminium alloy-low weight and shipment costs)

### Specifications:

Basic characteristic and equipment:

- Plexi doors with key lock
- Hinges

PART NUMBER	RACK UNIT	DIMENSIONS (H x W x D) mm	WEIGHT-empty box (kg)
OFDU-CAP-J	3U	133 x 432 x 305	1.9



OFDU-CAP-J: Typical fiber capacity		
Cassette	Number	Fibers (max.)
CAPM	1	12 (24)
CAPM	3	36 (72)
CAPM	6	72 (144)
CAPM	9	108 (216)
CAPM	12	144 (288)

Note: The CAPM is prewired cassette with pigtails and adapters (see the datasheet CMS\_22-01\_EN-CAPM)



OFDU-CAP-J with plexi door



View of backside of OFDU-CAP-J



Detail of hinges



View of side of cabinet

## Ordering code:

OFDU-CAP-J