


Outdoor Multitube Cable 12F (NC)

Description:

Outdoor Multitube Cable 12F (NC)

Rev. 0144-21/35

Full dielectric cable for external installation on cable trays or into duct by pulling



Specifications:

Fiber count	12
Fiber Type	G.652.D, G.657.A1, G.657.A2, G.655, G.656, OM1, OM2, OM2+, OM3, OM4
Fiber color	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua
Tube	Gel-Filled PBT buffer tube
Tube color	Blue
Tube filling compound	Low-viscosity filling gel
Central strength member	FRP rod
Core wrapping	Water-swellable tape
Peripheral strength members	Water-swellable glass yarns
Ripcord	1x under outer jacket
Outer jacket	UV resistant black HDPE
Jacket thickness	1.1 mm

Cable outer diameter	8.1	[mm]	
Tube count	1		
Filler count	5		
Max. Tensile Loading (Short Term)	1900	[N]	EN 60794-1-21-E1
Max. Tensile Loading (Long Term)	500	[N]	EN 60794-1-21-E1
Max. compressive loading	2000	[N]	EN 60794-1-21-E3
Max. Impact loading	10	[Nm]	EN 60794-1-21-E4
Min. bend radius (no load)	15	[OD]	EN 60794-1-21-E11
Min. bend radius (maximum load)	20	[OD]	EN 60794-1-21-E11
Operating temperature range	-40 to +70	[°C]	EN 60794-1-22-F1

Specifications are to change without notice. The information in this document must not be copied or reproduced without the prior written permission of the OPTOKON Kable Co., Ltd., s.r.o.

Storage temperature range	-40 to +70	[°C]	EN 60794-1-22-F1
Installation temperature range	-15 to +50	[°C]	EN 60794-1-22-F1
Water tightness	No water detected on free end		EN 60794-1-22-F5
Cable Weight (calc.)	52	[kg/km]	
Class of fire reaction	Fca		EN 13501-6a

Ordering code:

OPK-O-MTFDS-12(6x1.7)LTGP-xx-BK

xx - fiber type (see Cable code datasheet)

Marking Method: Ink-Jet

Print legend: OPK -cable type - lot number- length marking per 1 m (customer print legend available on request)

Delivery length: 2000 m, 4000 m ±5% on plywood reel or solid wooden non-returnable drum