


Outdoor Multitube Cable 96F (SC)

Description:

Outdoor Multitube Cable 96F (SC)

Rev. 0120-20/23

Full dielectric cable for external installation on cable trays or into duct by pulling



Specifications:

Fiber count	96
Fiber Type	G.652.D, G.657.A1, G.657.A2, G.655, G.656, OM1, OM2, OM2+, OM3, OM4
Fiber color	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua
Tube	Gel-Filled PBT buffer tube
Tube color	Blue, Orange, Green, Brown, Grey, White, Red, Black
Tube filling compound	Thixotropic Jelly Compound
Central strength member	PE coated FRP rod
Core wrapping	Water-swollable tape
Peripheral strength members	Water-swollable glass yarns
Ripcord	1x under outer jacket
Outer jacket	UV resistant black HDPE
Jacket thickness	1.5 mm

Cable outer diameter	11.4	[mm]
Tube count	8	
Filler count	0	
Max. Loading (Short Term)	2700	[N]
Max. Loading (Long Term)	1300	[N]
Max. compressive loading	2000	[N]
Max. Impact loading	20	[Nm]
Min. bend radius not load	15	[OD]
Min. bend radius load	20	[OD]
Operating temperature range	-40 to +70	[°C]

Specifications are to change without notice. The information in this document must not be copied or reproduced without the prior written permission of the OPTOKON Kable Co., Ltd., s.r.o.

Storage temperature range	-40 to +70	[°C]
Installation temperature range	-15 to +50	[°C]
Cable Weight (calc.)	91	[kg/km]
Class of fire reaction	Fca	
Test standards: EN 60790-1, EN 60794-1-21, EN 60794-1-22, EN 13501-6		

Ordering code:

OPK-O-MTFDS-96(8x2.0)LTGP-xx-BK

xx - fiber type (see Cable code datasheet)

Marking Method: Ink-Jet

Print legend: OPK -cable type - lot number- length marking per 1 m (customer print legend available on request)

Delivery length: 2100 m, 4200 m $\pm 5\%$ on plywood reel or solid wooden non-returnable drum