


Outdoor CST Armoured Multitube Cable-Double Jacket 144F (HC)

Description:

Outdoor CST Armoured Multitube Cable-Double Jacket 144F (HC)

Rev. 0170-20/32

Fibre optic cable with full protection against rodents for direct burial installation.



Specifications:

Fiber count	144
Fiber Type	G.652.D, G.657.A1, G.657.A2, G.655, G.656, OM1, OM2, OM3, OM4
Fiber color	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua
Tube	Gel-Filled PBT buffer tube
Tube color	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Aqua
Tube filling compound	Thixotropic Jelly Compound
Central strength member	PE coated FRP rod
Core wrapping	Water-swellable tape
Peripheral strength members	Water-swellable glass yarns
Inner jacket	UV resistant black LDPE
Inner jacket thickness	1.0 mm
Ripcord	1x under inner jacket
Armouring	Corrugated steel tape, longitudinally under jacket
Outer jacket	UV resistant black HDPE
Outer jacket thickness	1.5 mm

Cable outer diameter	19.0	[mm]
Tube count	12	
Filler count	0	
Max. Loading (Short Term)	5500	[N]
Max. Loading (Long Term)	2500	[N]
Max. compressive loading	5000	[N]

Max. Impact loading	30	[Nm]
Min. bend radius not load	15	[OD]
Min. bend radius load	20	[OD]
Operating temperature range	-40 to +70	[°C]
Storage temperature range	-40 to +70	[°C]
Installation temperature range	-15 to +50	[°C]
Cable Weight (calc.)	310	[kg/km]
Class of fire reaction	Fca	
Test standards: EN 60793-1, EN 60794-1-21, EN 60794-1-22, EN 13501-6		

Ordering code:

OPK-O-MTFDS-144(12x2.3)LTGPXP-xx-BK

xx - fiber type (see Cable code datasheet)

Marking Method: Ink-Jet

Print legend: OPK -cable type - lot number- length marking per 1 m (customer print legend available on request)

Delivery length: 2000 m $\pm 5\%$ on solid wooden non-returnable drum