

## MOTB-DG03 Termination Box

### Description:

Termination box MOTB-DG03 provides protection splice with optical fibre and pigtail, and can storage remaining cable inside the closure. Applying in the condition optical fiber connect into indoor termination. Termination box MOTB-DG03 is designed for FTTx application, which is suitable for jointing optical cables and pigtails, protects fiber optic splices and helps to distribute drop cables.



### Features:

- Compact design (450 x 150 x 180 mm)
- Free breathing box for indoor use
- In-line and butt configuration possible for main cable
- Wrap around cable seals for main cable and drops
- Not required to cut loop-through fibers from riser cable
- Compatible with mechanical splice and heat shrink protective sleeves
- LSZH material
- Transient free customer provisioning
- Drop cables are terminated individually
- Separate storage of un-connected fibers from spliced drop fibers
- Possibility to integrate PON splitters
- Main cable up to 16 mm
- Easy drop cable termination on strain relief device

### Specifications:

Model	Cable port	Spliced fiber storage capacity (single fusion)	PLC splitter	Adaptors	Protection class
MOTB-DG03	4 cable ports (for cables up to 16 mm diameter) +48 drop cable ports (3 mm)	144 splices (6 trays)	1:8, 1:16 PLC splitter	48x SC 48x DLC	IP54

### Physical parameters:

Outside Dimensions: 450 × 150 × 180 (mm)

Net weight: 2.3 kg


Sealing type: Mechanical

Working temperature: -40°C ÷ +65°C

Splicing capacity per splice tray: 24

Max. splice capacity (single fiber): 144

Material: ABS



Opened MOTB-DG03 termination box

Closed MOTB-DG03 termination box

**Ordering code:**

**MOTB-DG03 - XX - XX X**

<b># of Adaptors</b>
Up to 48

<b>Adaptors Type</b>			
<b>SC</b>	SC	<b>M</b>	Multimode
<b>DLC</b>	LC duplex	<b>S</b>	Single mode
		<b>A</b>	APC
		<b>X</b>	No adaptors