

OPT-SRI Wall Mounting Safe Rack IP65

Description:

Wall mounting safe racks OPT-SRI are designed for industrial applications. OPT-SRI racks provided IP65 protection class against dust and water ingress. Application areas are semi-open areas like factories, warehouses, lean-to roof conditions, where no direct rain and environmental effects. Totally gasketed door, IP65 performing casted handled locking with one point or three point locking system, isolated cable entries provides the best performance on the water and dust ingress.

t=1,5mm thickness material, monoblock welded construction, with epoxy polyester, type powder coating which is RAL 7035 light grey color or optional RAL9005 black color, provides the corrosion resistance.



Features:

- Width : 600 mm.
- Depth : 400/500/600 mm.
- RAL 7035, optionally other colors
- Grounding set is as standard accessories
- Optional additional accessories (shelves, PDU, light, fans, roof, etc.)

Specifications:



Opened OPT-SRI rack




Closed OPT-SRI rack



Roof



Skeleton edge detail

Pitch of holes for wall mounting
' (rear part of the rack):

Casted Iron Handled Locking with 3point locking system provides security and anti-vandal structure, where helps maintaining the IP65 protection.

Grounded front door to the main body with yellow/green 4,0 mm diameter copper wire.

Front door has the strengthening bar welded inside part of the front door, 2 pcs U Shaped.


19" rails of OPT-SRI OPTOKON rack are with automated silk-screen U numbering, depends on size 4U to 28U, same from top to bottom or bottom to top results to same U height selection. No matter from where you have started counting.

19" rails are 4 fold bending surfaces, 1,5mm thickness provides the high load capacities.


19" rails are made of steel with 8-12 micron zinc plating for corrosion resistance. 19" rails are adjustable in depth.

Cabinets are delivered with 1set: 2 pcs 19" rails in front.

The front door is being closed on gasketing system on the flange bends of the enclosure body. Included 4 pcs, t: 3,0 mm thickness wall fixing brackets with proper washer and screws.




FRONT VIEW




SIDE VIEW




REAR VIEW



TOP VIEW



INSIDE VIEW



3 POINT LOCKING SYSTEM

Accessories:

- PDU (Power distribution units).
- Shelves
- Light
- Fans
- Roof
- 1U Fiber Management Panel

Ordering code:

OPT-SRI	- 65	- 15U	- x	- X
	Size (Width+Depth)	Height (Unit)	Colour G (Grey) RAL7035 B (Black) RAL9005	Lock L 1 point locking system 3L 3 point locking system

Products with depth 600 mm

Product number	Description	Height (U)	Height (mm)	Width (mm)	Depth (mm)
OPT-SRI-66-04U-x-X	4U 19" Wall mounting rack, IP65	4	245	600	600
OPT-SRI-66-06U-x-X	6U 19" Wall mounting rack, IP65	6	335	600	600
OPT-SRI-66-09U-x-X	9U 19" Wall mounting rack, IP65	9	470	600	600
OPT-SRI-66-12U-x-X	12U 19" Wall mounting rack, IP65	12	600	600	600
OPT-SRI-66-15U-x-X	15U 19" Wall mounting rack, IP65	15	735	600	600
OPT-SRI-66-18U-x-X	18U 19" Wall mounting rack, IP65	18	870	600	600
OPT-SRI-66-21U-x-X	21U 19" Wall mounting rack, IP65	21	1000	600	600
OPT-SRI-66-24U-x-X	24U 19" Wall mounting rack, IP65	24	1135	600	600
OPT-SRI-66-28U-x-X	28U 19" Wall mounting rack, IP65	28	1315	600	600

Products with depth 500 mm

Product number	Description	Height (U)	Height (mm)	Width (mm)	Depth (mm)
OPT-SRI-65-04U-x-X	4U 19" Wall mounting rack, IP65	4	245	600	500

OPT-SRI-65-06U-x-X	6U 19" Wall mounting rack, IP65	6	335	600	500
OPT-SRI-65-09U-x-X	9U 19" Wall mounting rack, IP65	9	470	600	500
OPT-SRI-65-12U-x-X	12U 19" Wall mounting rack, IP65	12	600	600	500
OPT-SRI-65-15U-x-X	15U 19" Wall mounting rack, IP65	15	735	600	500
OPT-SRI-65-18U-x-X	18U 19" Wall mounting rack, IP65	18	870	600	500
OPT-SRI-65-21U-x-X	21U 19" Wall mounting rack, IP65	21	1000	600	500
OPT-SRI-65-24U-x-X	24U 19" Wall mounting rack, IP65	24	1135	600	500
OPT-SRI-65-28U-x-X	28U 19" Wall mounting rack, IP65	28	1315	600	500

Products with depth 400 mm

Product number	Description	Height (U)	Height (mm)	Width (mm)	Depth (mm)
OPT-SRI-64-04U-x-X	4U 19" Wall mounting rack, IP65	4	245	600	400
OPT-SRI-64-06U-x-X	6U 19" Wall mounting rack, IP65	6	335	600	400
OPT-SRI-64-09U-x-X	9U 19" Wall mounting rack, IP65	9	470	600	400
OPT-SRI-64-12U-x-X	12U 19" Wall mounting rack, IP65	12	600	600	400
OPT-SRI-64-15U-x-X	15U 19" Wall mounting rack, IP65	15	735	600	400
OPT-SRI-64-18U-x-X	18U 19" Wall mounting rack, IP65	18	870	600	400
OPT-SRI-64-21U-x-X	21U 19" Wall mounting rack, IP65	21	1000	600	400
OPT-SRI-64-24U-x-X	24U 19" Wall mounting rack, IP65	24	1135	600	400
OPT-SRI-64-28U-x-X	28U 19" Wall mounting rack, IP65	28	1315	600	400

Note: 4U and 6U height is not produced with 3 point locking system.