

## QUICK-CURE Quick installable connectors

### Description:

QUICK-CURE™ introduces a new type of optical connector for use in field conditions. The pre polished connector (SC, LC type) is designed for optical fiber termination especially in FTTH projects, directly in the end user site. Using the tool kit containing all necessary tools, it allows easy optical network installation. Termination with no epoxy, no heating, no polishing and no splicing achieves similar excellent transmission parameters as standard polishing and splicing technology.

Connector set for various fiber and cable diameter is available.



QUICK-CURE™ helps you save time when working in the field.

### Features:

- FTTH project usable
- Field installable, quick assembly time
- Cost effective, User friendly
- No electricity required No epoxy and polishing required
- Precision mechanical alignment insures low insertion loss
- Users proven, molded v-groove technologies

### Specifications:

Fiber type	Single mode, G.652D & G.657A1 (typical/maximal)
Insertion Loss <sup>1</sup>	0.3 dB / 0.50 dB
Return Loss <sup>2</sup>	≥ 45 dB (UPC) / ≥ 60 dB (APC)
Polishing type	UPC / APC
Reusable	≥ 5 times
Fastening strength of bare fiber	≥ 5 N
Tensile strength	≥ 50 N
On-line tensile strength (20 N) ΔIL ≤ 0.3 dB	ΔIL ≤ 0.3 dB
Mechanical durability (500 times)	ΔIL ≤ 0.3 dB

Drop-off test (drop-off height 4 m, once per direction, totally 3 times)	$\Delta IL \leq 0.3 \text{ dB}$
Operational temperature	-30 °C to 75 °C
Connection method	Push - On

Note:

- 1) Installation by trained staff
- 2) APC  $\geq 60 \text{ dB}$  (room temperature),  $\geq 35 \text{ dB}$  (temperature -40 to +70 °C)

SC connector



0.9/2.0/3.0 fiber-cable

LC connector



0.9 fiber



3.0 cable

### QUICK-CURE™ tool kit content OSK-QCF-100:

- Assembly manual
- Tools and Consumables

Hard carrying case




Fiber cleaver OCL-100



Isopropyl alcohol



Kevlar cutter



Cable jacket stripper  
(3 mm, 2.4 mm)



Lint-free tissue



Marking pen



Universal Miller stripper  
(0.9 mm, 250  $\mu\text{m}$ )



**Application:**

- FTTH - PON, LAN, WAN

**Ordering code:**

**XXX-QF**

**- XX**

**- XX**

**XXX - Connector**

<b>SC</b>	SC/PC (MM)
<b>USC</b>	SC/PC (SM)
<b>NSC</b>	SC/APC (SM)
<b>LC</b>	LC/PC (MM)
<b>ULC</b>	LC/PC (SM)
<b>NLC</b>	LC/APC (SM)

**Fiber type**

<b>OM1</b>	MM 62.5/125 $\mu$ m
<b>OM2-4</b>	MM 50/125 $\mu$ m
<b>SM</b>	G.652D & 657A1

**Boot type**

<b>09</b>	fiber $\varnothing$ 0.9 mm
<b>30</b>	cable $\varnothing$ 3.0 mm